

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
1 March 2001 (01.03.2001)

PCT

(10) International Publication Number  
WO 01/14039 A1(51) International Patent Classification<sup>7</sup>: B01D 24/02

(21) International Application Number: PCT/US00/23155

(22) International Filing Date: 23 August 2000 (23.08.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/150,872 26 August 1999 (26.08.1999) US(71) Applicant (for all designated States except US): THE  
PENN STATE RESEARCH FOUNDATION [US/US];  
304 Old Main, University Park, PA 16802-7000 (US).

(72) Inventor; and


(75) Inventor/Applicant (for US only): XIE, Yuefeng  
[CN/US]; 754 Fieldstone Lane, Elizabethtown, PA 17022  
(US).(74) Agent: MONAHAN, Thomas, J.; Intellectual Property  
Office, The Pennsylvania State University, 113 Technology  
Center, University Park, PA 16802-7000 (US).(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,  
DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,  
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,  
LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,  
NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM,  
TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian  
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European  
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,  
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,  
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD OF USING WASTE TIRES AS A FILTER MEDIA

(57) Abstract: The present invention is a method of using crumb rubber  
from recycled tires as a filter media. The use of crumb rubber as a media  
differs from conventional sand or anthracite filters in several ways. The  
crumb rubber media is compressible which allows the porosity between  
rubber particles to decrease through the filter bed. The crumb rubber me-  
dia compresses as headloss increases, allowing for better effluent quality  
late in the run. The crumb rubber media allows greater depth filtration.  
The crumb rubber media can be used at high filter rates, greater than 20  
gpm/ft<sup>2</sup>. The crumb rubber media performs similarly to other traditional  
filter media in respect to turbidity and total suspended solids removal. The  
crumb rubber media properties are closely tied to media size and shape,  
with smaller media providing better effluent qualities and larger media  
allowing longer filter runs at higher flow rates.

WO 01/14039 A1